

PRESENTS

LED P3 & P6 Standee.



ALPHA TECHNOCRATZ PRODUCTS
L-96, STREET NO. 7 , MAHIPALPUR
NEW DELHI-110037
chetan@technocratz.in
www.technocratz.in
8505870707, 9810124109

SUB: Plug and play LED P3 Indoor & P6 Outdoor Standee

These are standalone single cabinet Plug and play systems and require only the simple software to be installed on PC and you can connect Video screen directly to PC or load data via Pen Drive or wireless from PC / Android mobile (if on same network)

Standee 2 feet x 6 feet				
Display area WxH	Model	P3 Indoor	Model	P6 Outdoor
2' x 2.5' (576 x 768mm)	STAN3-01	Rs. 56,000/-	STAN6-01	Rs. 44,000/-
2' x 3' (576 x 960mm)	STAN3-02	Rs. 65,500/-	STAN6-02	Rs. 51,000/-
2' x 4' (576 x 1152mm)	STAN3-03	Rs. 73,000/-	STAN6-03	Rs. 55,500/-
2' x 4.5' (576 x 1344mm)	STAN3-04	Rs. 83,000/-	STAN6-04	Rs. 60,500/-
2' x 5' (576 x 1536mm)	STAN3-05	Rs. 91,000/-	STAN6-05	Rs. 67,500/-
2' x 5.5' (576 x 1728mm)	STAN3-06	Rs. 1,00,500/-	STAN6-06	Rs. 72,000/-
2' x 6' (576 x 17920mm)	STAN3-07	Rs. 1,08,000/-	STAN6-07	Rs. 79,500/-
Standee 2.5 feet x 6 feet				
Display area WxH	Model	P3 Indoor	Model	P6 Outdoor
2.5' x 2.5' (768 x 768mm)	STAN3-08	Rs. 71,000/-	STAN6-08	Rs. 55,000/-
2.5' x 3' (768 x 960mm)	STAN3-09	Rs. 83,500/-	STAN6-09	Rs. 62,000/-
2.5' x 4' (768 x 1152mm)	STAN3-10	Rs. 94,000/-	STAN6-0	Rs. 70,500/-
2.5' x 4.5' (768 x 1344mm)	STAN3-11	Rs. 1,06,000/-	STAN6-11	Rs. 77,000/-
2.5' x 5' (768 x 1536mm)	STAN3-12	Rs. 1,16,500/-	STAN6-12	Rs. 85,500/-
2.5' x 5.5' (768 x 1728mm)	STAN3-13	Rs. 1,29,000/-	STAN6-13	Rs. 92,000/-
2.5' x 6' (768 x 1920mm)	STAN3-14	Rs. 1,41,000/-	STAN6-14	Rs. 1,00,500/-
Standee Larger Sizes				
2.5' x 8' (768 x 2304mm)	STAN3-15	Rs. 1,72,500/-		
3' x 9' (960 x 2688mm)			STAN6-15	Rs. 1,70,000/-

Full color LED video display (RGB)

NO.	Parameter	P6 SMD Outdoor	P3 SMD Indoor
1	Pixel Pitch	6mm	3mm
2	Physical density	27777dot/m ²	111111dot/m ²
3	Pixel configuration	SMD3535	SMD2121
4	Brightness (cd/m ²)	≥6500	≥2300
5	Half light Angle (horizontal/vertical)	140° / 70°	140° / 70°
6	Viewing Angle (H/W)	160° / 140°	160° / 140°
7	gray scale	65536	65536
8	Color	16.7 million	16.7 million
9	color temperature	6500-7000K	6500-7000K
10	refresh rate	350Hz	400 Hz
11	contrast	4000:1	4000:1
12	repetition frequency	60HZ/S	60HZ/S
13	MTBF	1000 h	1000 h
14	Life span	100,000 hours	100,000 hours
15	maximum power consumption	800w/m ²	1000w/m ²
16	Average power consumption	400w/m ²	460w/m ²
17	Driving IC	1/8, constant current	1/16, constant current
18	Lamp failure frequency	≤0.1‰	≤0.1‰
19	control mode	Synchronization with the video source	
20	Working Voltage1	AC90-240V	AC90-240V
21	Working Voltage2	DC5V	DC5V
22	Working temperature	-20~50°C	-20~50°C
23	Working Humidity	10%~90%	10%~90%
24	Cabinet material	MS Powder coated	MS Powder coated
25	Module Size (L*H)	192mmx192mm	192mmx192mm
26	Module Resolution (L*H)	32 X 32	64 X 64
27	Module current	5A	5A
28	Module Weight	280g	300g
29	Module port	hub75	hub75

